




### REL.33A/35A Rim Exit Device Standard Trim

	Exit Only	Dummy Trim Pull when Device is Dogged	Night Latch Key Retracts Latch Bolt	Night Latch Key Retracts Latch Bolt Optional Pull Required
				
<b>Product Description</b>	REL.33A-EO REL.35A-EO	REL.33A-DT REL.35A-DT	REL.33A-NL REL.35A-NL	REL.33A-NL-OP REL.35A-NL-OP
<b>Trim Description</b>	-	REL.386DT	REL.386NL	REL.388
<b>Base Size</b>	-	190mm x 41mm	190mm x 41mm	190mm x 43mm
<b>Grip Size</b>	-	216mm x 110mm	216mm x 110mm	-
<b>Projection</b>	-	62mm	62mm	25mm
<b>Cylinder Type</b>	-	-	Rim - REL.20-022	Rim - REL.20-022

	Lever Key Locks & Unlocks Trim	Lever Blank Escutcheon Always Operable (No Cylinder)	Thumbturn Key Locks & Unlocks Trim
			
<b>Product Description</b>	REL.33A-L REL.35A-L	REL.33A-L-BE REL.35A-L-BE	REL.33A-T REL.35A-T
<b>Trim Description</b>	REL.360L	REL.360L-BE	REL.360T
<b>Base Size</b>	190mm x 43mm x 22mm	190mm x 43mm x 22mm	190mm x 43mm x 22mm
<b>Grip Size</b>	-	-	-
<b>Projection</b>	76mm	76mm	46mm
<b>Cylinder Type</b>	Mortice - REL.20-001.114	-	Mortice - REL.20-001.114

**REL.20-022C.626**  
C Section Rim Cylinder -  
Satin Chrome. Supplied with  
2 keys normally.



**REL.20-001C.626**  
C Section Mortice Cylinder -  
Satin Chrome. Supplied with  
2 keys normally.



#### Important Note

Cylinders must be ordered separately for all trims where appropriate.

#### Trim Operation Options

For all cylinder operated trims shown here the key locks and unlocks the lever/thumbturn, in turn the lever or thumbturn retracts the latch - referred to as the **classroom function**. This function uses the 'dogged' mortice cylinder straight cam (See page 25).

For a true night latch function use the 'undogged' mortice cylinder straight cam - the key retracts the latch - referred to as the **storeroom function** (See page 25).