




REL.22 Rim Exit Device Standard Trim

	Exit Only	Dummy Trim Pull when Device is Dogged	Night Latch Key Retracts Latch Bolt	Night Latch Key Retracts Latch Bolt Optional Pull Required
				
Product Description	REL.22EO	REL.22DT	REL.22NL	REL.22NL-OP
Trim Description	-	REL.210DT	REL.210NL	REL.110NL
Escutcheon Plate Size	-	137mm x 121mm x 2mm	137mm x 121mm x 2mm	-
Projection	-	42mm	42mm	-
Cylinder Type	-	-	Rim - REL.20-022	Rim - REL.20-022
Optional REL.425 Sex Bolt Qty for Device	6	2	2	6

	Thumb Piece Key Locks & Unlocks Trim	Lever Key Locks & Unlocks Trim	Night Latch Key Retracts Latch Bolt
			
Product Description	REL.22TP	REL.22L	REL.22NL(230)
Trim Description	REL.230TP	REL.230L	REL.230NL
Escutcheon Plate Size	76mm x 306mm x 2mm	76mm x 162mm x 24mm	76mm x 306mm x 2mm
Projection	51mm	67mm	51mm
Cylinder Type	Mortice - REL.20-001.114	Mortice - REL.20-001.114	Rim - REL.20-022
Optional REL.425 Sex Bolt Qty for Device	2	2	6

REL.20-022C.626
C Section Rim Cylinder -
Satin Chrome. Supplied with
2 keys normally.



REL.20-001C.626
C Section Mortice Cylinder -
Satin Chrome. Supplied with
2 keys normally



Important Note

Cylinders must be ordered separately for all trims where appropriate.

The REL.210DT/210NL/230TP/230NL have heavy gauge 2.4mm steel escutcheons.

The REL.230L has a cast aluminium 19mm escutcheon with #06 style lever furnished standard. The #03 style lever is available to special order - handing of the lever is field reversible.