



TRIM - LOCKS



2-669-0644 **Replacement Rose Kit**

Application: For use with Euroline deadlock mortise locks
 Material: Stainless steel
 Finish: US32D
 Dimensions: 54 mm diameter
 10 mm width
 Fasteners: Two (2) M4 x 60 mm FPHMS with sex nuts plus
 four (4) 4 mm x 22 mm FPHWS



2-669-0645/2-669-1363 **Lever Spindle Extension Kit**

Application: For use on doors 50 mm thick to 63.5 mm thick
 Models: 2-669-0645; used with circular rose levers
 2-669-1363; used with square rose levers
 Material: Steel
 Includes: One (1) extension shaft and four (4) M4 x 75 mm screws with sex nuts



2-669-0735 **Strike Dust Box**

Application: For use with Euroline mortise lock strike plates
 Material: Plastic (white)
 Includes: One (1) dust box



2-669-0736 **Bathroom Turn Indicator with Emergency Release**

Application: For use with 3800U-55B bathroom mortise lock
 Rose Diameter: 52 mm
 Rose Thickness: 4 mm
 Knob Projection: 27 mm
 Door Thickness: 51 mm maximum
 Material: Stainless steel
 Finish: US32D
 Fasteners: Four (4) 3.5 mm x 25 mm

TRIM - LOCKS



2-669-0732

Half Spindle

Length:

Notes:

58 x 8 x 8 mm

- Used with 3800U-55M and 3800U-55T mortise night latches
- Hook at spindle head ensures secure fit when used with half lever sets



2-669-0733

Split Spindle

Length:

Notes:

52.5 x 8 x 8 mm each spindle

105 mm total length

- Used with 3800U-55P mortise anti-panic split follower locks
- Enables independent operation on inside and outside of doors



2-669-1364

Blank Cylinder Rose

Material:

Finish:

Dimensions:

Notes:

Stainless steel

US32D

54 mm diameter

10 mm width

For Euroline mortise locks using half cylinders



3910

Padlock

Material:

Body Width:

Body Height:

Body Thickness:

Cylinder:

Shackle Height:

Shackle Diameter:

Keyway:

Keying:

Includes:

Notes:

- Body - steel
- Shackle - hardened steel

44 mm

56.2 mm

22.8 mm

Removable

34.5 mm

8 mm

Schlage C

- Keyed Different (KD) - Standard
- Master Key (MK) - Optional

One (1) padlock with removable cylinder and two (2) brass keys

Spring loaded shackle