

Patch Fittings



Patch fittings allow for the hanging and operation of glass doors in conjunction with floor springs and locking systems. Hager Companies provides a comprehensive range of patch fittings and pivot assemblies to work seamlessly with their floor springs and euro cylinders.



PATCH FITTINGS



651

Bottom Patch Fitting

Glass Thickness:

Material:

Maximum Door Weight:

Maximum Door Width:

Handing:

Finish:

Includes:

Installation:

Notes:

10-12 mm

- Cast aluminum base
- Stainless steel cover

80 kg

1100 mm

Suitable for left and right hand door (double acting)

US32

One (1) patch fitting and one (1) allen key

Clamp fixing, concealed with hexagonal socket screws

- Pivot post hole for use with all Hager 5800 floor closers
- Pivot laterally adjustable +/- 3 mm



652

Top Patch Fitting

Glass Thickness:

Material:

Maximum Door Weight:

Maximum Door Width:

Handing:

Finish:

Includes:

Installation:

Notes:

10-12 mm

- Cast aluminum base
- Stainless steel cover

80 kg

1100 mm

Suitable for left and right hand door (double acting)

US32

One (1) patch fitting and one (1) allen key

Clamp fixing, concealed with hexagonal socket screws

- Pivot post bearing for use with upper and corner over panel patch fitting
- Pivot laterally adjustable +/- 3 mm



653

Overpanel Patch Fitting

Glass Thickness:

Material:

Maximum Door Weight:

Maximum Door Width:

Handing:

Finish:

Includes:

Installation:

Notes:

10-12 mm

- Cast aluminum base
- Stainless steel cover

80 kg

1100 mm

Suitable for left and right hand door (double acting)

US32

One (1) patch fitting and one (1) allen key

Clamp fixing, concealed with hexagonal socket screws

- Pivot post for use with top patch fitting
- Pivot laterally adjustable +/- 3 mm



PATCH FITTINGS



654

Corner Overpanel Patch Fitting

- Glass Thickness: 10-12 mm
- Material:
- Cast aluminum base
 - Stainless steel cover
- Maximum Door Weight: 80 kg
- Maximum Door Width: 1100 mm
- Handing: Suitable for left and right hand door (double acting)
- Finish: US32
- Includes: One (1) patch fitting and one (1) allen key
- Installation: Clamp fixing, concealed with hexagonal socket screws
- Notes:
- Pivot post for use with top patch fitting
 - Pivot laterally adjustable +/- 3 mm



655

Bottom Lock Patch Fitting

- Glass Thickness: 10-12 mm
- Material:
- Cast aluminum base
 - Stainless steel cover
- Handing: Suitable for left and right hand door (double acting)
- Finish: US32
- Includes: Patch fitting, allen key, floor strikes hardware, Schlage C cylinder and three (3) keys
- Installation: Clamp fixing, concealed with hexagonal socket screws



2-659-0150

Heavy Duty Top Pivot

- Material: Cast aluminum base
- Finish: US15 top pivot cover plate
- Includes:
- One (1) frame pivot
 - One (1) stainless steel US15 frame pivot cover with mount screws
 - Mounting hardware screw bag
- Installation: Vertically adjustable pivot pin for easy door installation
- Notes: For use with 652 and non-glass frames

