

Table Of Contents

Lock Guards	page
LG1, LG7 Lock Guard	F2
LG10 Lock Guard	F2
LG11 Lock Guard	F3
LG12 Lock Guard	F3
LG13 Lock Guard	F4
LG14 Lock Guard	F4
Viewers	
U696 One-way Viewer	F5
698, U698 One-way Viewer	F5
700, U700 One-way Viewer	F6
701, U701 One-way Viewer	F6
Door Knockers	
3107 Door Knocker	F7
3125 Door Knocker	F7
Letter Box	
620 Letter Box Plate	F8
601 Letter Box Sleeve	F8
Door Numbers	
02-30 Door Numbers	F9
Storm and Screen Door	
980 Storm Door Latch	F9
25 Screen Door Pull	F10
Crash Stop	
CS115 Crash Stop	F10



A
Hinges & Pivots

B
Pulls & Plates

C
Flush Bolts & Coordinators

D
Latches, Catches & Bolts

E
Stops

F2
Exterior Hardware

G
Miscellaneous Hardware



LG1 Lock Guard

- Units are non-handed and incorporate security frame pin to prevent separation of the door and frame. LG7 does not incorporate the security frame pin
- Unit covers the latch bolt area of the door and lock, thereby providing added protection from burglars, vandals or normal abuse.
- Ideal for use with mortise or cylindrical locks.
- Easy installation.
- Through bolted with carriage bolts and nuts.
- Available in a variety of materials, 13 gauge stainless steel, 12 gauge steel and brass material.

Dimensions

3" Wide x 11-1/2" High

Bolt center to center: 10-1/2"

Finishes

Ives Number	USP*	US2G*	US4*	US10*	US32D	SP313*
BHMA	600	603	606	612	630	695

* not available on LP7



LG10 Lock Guard

- Ideally suited for use with rose or escutcheon 2-3/4" wide or less.
- For use with Type 86 Mortise and Type 161 Cylindrical Locks (ANSI 156.13 Series 1000 and ANSI 156.2 Series 4000).
- No exposed fasteners on face of unit.
- Unique design provides maximum security, virtually eliminating the opening between door and frame at the latch point.
- Available in 13 Gauge Stainless Steel or 12 Gauge Steel.

Dimensions

2-1/2" Wide x 9-1/2" High

Stud center to center: 8-1/2"

Finishes

Ives Number	USP	US32D
BHMA	600	630



LG11 Lock Guard

- Designed for use on aluminum doors with latch-type locks or doors equipped with electric strikes.
- Unit is Handed - Specify left or right hand when ordering.
- No exposed fasteners on face of unit.
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point.
- Available in 13 Gauge Stainless Steel or 12 Gauge Steel.

Dimensions

2-1/2" Wide x 9-1/2" High
Stud center to center: 8-1/2"

Finishes

Ives Number	US32D	SP313
BHMA	630	695



LG12 Lock Guard

- Narrow design unit for use on rose or escutcheon 3-1/2" or less.
- For use with Type 86 Mortise and Type 161 Cylinder Locks (ANSI 156.13 Series 1000 and ANSI 156.2 Series 4000).
- No exposed fasteners on face of unit.
- Unique design provides maximum security, virtually eliminating the opening between door and frame at the latch point.
- Available in 13 Gauge Stainless Steel or 12 Gauge Steel

Dimensions

1-1/2" Wide x 9-1/2" High
Stud center to center: 8-1/2"

Finishes

Ives Number	USP	US32D
BHMA	600	630

A
Hinges & Pivots

B
Pulls & Plates

C
Flush Bolts & Coordinators

D
Latches, Catches & Bolts

E
Stops

F3
Exterior Hardware

G
Miscellaneous Hardware



LG13 Lock Guard

- Designed for use on all Type 161 Cylindrical Locks (ANSI 156.2 Series 2000) Monolock and Unilock.
- No exposed fasteners on face of unit.
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point.
- Available in 13 Gauge Stainless Steel or 12 Gauge Steel.

Dimensions

1-1/2" Wide x 7" High

Stud center to center: 4-1/2"

Finishes

Ives Number	USP	US32D
BHMA	600	630



LG14 Lock Guard

- Narrow design unit for use on rose or escutcheon 3-1/2" or less.
- For use with Von Duprin 6210 and 6211 electric strike.
- No exposed fasteners on face of unit.
- Unique design provides maximum security.
- Available in 13 Gauge Stainless Steel

Dimensions

2-9/16" Wide x 9-1/2" High

Stud center to center: 8-1/2"

Finishes

Ives Number	US32D
BHMA	630



Meets ANSI/BHMA A156.16 L23222
UL Listed 90 minute fire doors

U696 One-Way Viewer

- 150° Angle of View.
- For doors 1-3/8" to 2-1/16" thick.
- Secure, tamper-resistant.
- Solid brass body; glass lens.
- Simple installation — only a 1/2" hole required.
- Suggested installation height: 60" from floor.
- Trim washer available, 3/4" x .032" thick.

Finishes

Ives Number	B4	B10B	B26D
BHMA	606	613	626



698 meets ANSI/BHMA A156.16 L23172
U698 meets ANSI/BHMA A156.16 L23222
U698 is UL Listed 90 minute fire doors

698 U698 One-Way Wide Angle Viewer

- 190° Angle of View.
- Lens projects 1/4" from face of door.
- 4 optical glass lenses.
- For doors 1-3/8" to 2-1/8" thick.
- Solid brass body and barrel.
- Simple installation — only a 9/16" hole required.
- Suggested installation height: 60" from floor.

Finishes

Ives Number	B3	B15**	B26D	B716*
BHMA	605	619	626	

* not available on U698

** only available in Schlage Carded

A
Hinges & Pivots

B
Pulls & Plates

C
Flush Bolts & Coordinators

D
Latches, Catches & Bolts

E
Stops

F5
Exterior Hardware

G
Miscellaneous Hardware

A

Hinges & Pivots

B

Pulls & Plates

C

Flush Bolts & Coordinators

D

Latches, Catches & Bolts

E

Stops

F6

Exterior Hardware

G

Miscellaneous Hardware



700 U700 One-Way Viewer

- 120° Angle of View.
- For doors 1-3/8" to 2-1/16" thick.
- Secure, tamper-resistant.
- Solid brass body; glass lens.
- Simple installation—only a 1/2" hole required.
- Suggested installation height: 60" from floor.
- Trim washer available, 3/4" x .032" thick.

Finishes

Ives Number	B3**	B4	B10B*	B26D
BHMA	605	606	613	626

* not available on U700

** only available on 700 in Schlage Carded

700 meets ANSI/BHMA A156.16 L23173
U700 meets ANSI/BHMA A156.16 L23222
U700 is UL Listed 90 minute fire doors



701 U701 One-Way Viewer

- 120° Angle of View.
- For doors 2-1/8" to 2-5/8" thick.
- Secure, tamper-resistant.
- Solid brass body; glass lens.
- Simple installation—only a 1/2" hole required.
- Suggested installation height: 60" from floor.
- Trim washer available, 3/4" x .032" thick.

Finishes

Ives Number	B4	B10B	B26D
BHMA	606	613	626

701 meets ANSI/BHMA A156.16 L23173
U701 meets ANSI/BHMA A156.16 L23222
U701 is UL Listed 90 minute fire doors.



Meets ANSI/BHMA A156.16 L23151

02-3107 Knocker Only

- Knocker made from forged brass.
- Only available in Schlage Carded pak

Dimensions

Length: 8-1/2"

Width: 4-1/8"

Projection: 1"

Mounting Hole Center-to-Center: 5"

Finishes

Ives Number	B605	B19
BHMA	605	619

02-3125 Knocker Only 02-31251U Knocker with U700 Viewer 02-31252U Knocker with U701 Viewer

- Knocker made from forged brass.
- 02-31251 and 02-31251U for door thickness 7/8" – 1-9/16"
- 02-31252 and 02-31252U for door thickness 1-5/8" – 2-1/8"

Dimensions

Length: 5-15/16"

Width: 3"

Projection: 1-1/16"

Mounting Hole Center-to-Center: 3-15/16"

Finishes

Ives Number	B3	B5	B15	B15A*	B26	B26D	716
BHMA	605	609	619	620	625	626	

* not available on viewer, only available in Schlage Carded

Only B3, B15, B26D and 716 knockers are available with viewer. B3 is furnished with B4 (606) viewer, 716 is furnished with B10B viewer, B15 (619) is furnished with a 636 viewer.



Meets ANSI/BHMA A156.16 L23161

A
Hinges & Pivots

B
Pulls & Plates


C
Flush Bolts & Coordinators

D
Latches, Catches & Bolts

E
Stops

F7
Exterior Hardware

G
Miscellaneous Hardware



Meets ANSI/BHMA A156.16 L26031

620

Magazine Size Letter Box Plate with Standard (Open) Back Plate

- Spring-loaded front plate
- Sex Bolt mounting available, order separately 09-355 – finish.

Dimensions

Overall Size: 13" Wide x 3-9/16" High

Plate Opening: 11" x 2" High

Finishes brass

Ives Number	B3	B5	B15	B15A*	B26	B26D	B716
BHMA	605	609	619	620	625	626	

Finishes aluminum

Ives Number	PA28
BHMA	628

* not available in U700 Schlage Carded



601

Sleeve for use with Letter Box Plate

- Made of stainless steel.
- For 1-3/4" hollow core doors.

**SC2 - 30 X 6 Heritage House Number**

- Made from solid brass.
- Schlage Carded*

0 - 3006	5 - 3056
1 - 3016	6 - 3066
2 - 3026	7 - 3076
3 - 3036	8 - 3086
4 - 3046	9 - 3096

Dimensions

Height: 4"

Finishes *brass*

Ives Number	B3	B15	B716
BHMA	605	619	

**980 Storm Door Latch**

- For wood storm doors 7/8" to 1-1/8" thick.
- Reversible: fits right or left hand, inswinging or outswinging doors.
- Security lock feature operates from inside rose.
- Solid brass safety strike assures latching and is designed to compensate for air pressure build-up between doors.
- Made from wrought brass.

Dimensions

Backset: 1-3/4"

Rose Diameter: 1-7/8"

Knob Diameter: 1-3/4"

Knob Projection: 2"

Lever Length: 1-3/4"

Lever Projection: 1-7/8"

Finishes *brass*

Ives Number	B3	B5	B10B	B15	B19	B26	B26D
BHMA	605	609	613	619	622	625	626

A
Hinges & PivotsB
Pulls & PlatesC
Flush Bolts & CoordinatorsD
Latches, Catches & BoltsE
StopsF9
Exterior HardwareG
Miscellaneous Hardware

A
Hinges & Pivots

B
Pulls & Plates

C
Flush Bolts & Coordinators

D
Latches, Catches & Bolts

E
Stops

F10
Exterior Hardware

G
Miscellaneous Hardware



Meets ANSI/BHMA A156.16, L12231,

25 Screen Door Pull

- Cast aluminum or epoxy-coated aluminum
- Also used as a window lift, drawer or utility pull

Dimensions

Length 4-7/8"

Projection 1-5/32"

Mounting holes 4-1/8" center to center

Finishes

Ives Number	A3	A92	A-W	A-B
BHMA	666	673		



Meets ANSI/BHMA A156.16, L12231,

CS115 Crash Stop

- Specially designed for full-size exterior doors.
- Tear resistant, grey vinyl cover.
- Heavy duty compression spring assembled to both ends of chain and end brackets.
- Packed with sheet metal screws.
- Cast Brass brackets with solid, welded steel chain.
- Optional sex bolt mounting available in US26D (626) only.

Dimensions

Bracket Size: 1-9/16" x 1-9/16"

Available Lengths:

20-1/2" — Recommended for 30" Door Width (Product No. CS115-20)

25-1/2" — Recommended for 36" Door Width (Product No. CS115-25)

30-1/2" — Recommended for 42" Door Width (Product No. CS115-30)

Finishes

Ives Number	US10B	US26D
BHMA	613	626